



14" Diameter 4.80/4.00-8 Wheel (Light Duty)

Light weight replacement wheel for light duty wheelbarrows and wagons, etc.

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
W-2	14.250"	3.75"	Rib	8"	6"	250 lbs.

Standard: 1pc centered wheel hub with 5/8" ball bearings & grease fitting

Options: Wheel Hubs - 3", 4" centered with 1/2", 5/8", or 3/4" bearings

Colours: Black only



15" Diameter 480/400-8 Wheel (Standard Duty)

Great replacement wheel for 5 and 6 cubic feet wheelbarrows. Ideal for new equipment, construction rentals, maintenance crews equipment, landscapers, homeowners, etc.

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
W-1	15.50"	3.75"	Rib	8"	6"	400 lbs.

Standard: 1pc centered wheel hub with 5/8" ball bearings & grease fitting

Options: Wheel Hubs - 3", 4" centered with 1/2", 5/8", or 3/4" bearings

Colours: Red, Blue, Green, Yellow, Orange, and Black



15" & 16" Diameter 480/400-8 Wheel (Heavy Duty)

This Heavy Duty Wheel is designed to handle loads up to 595 lbs. Ideal for construction trades that manually haul heavy loads of concrete, earth and stone.

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
W-1HD 500	15.50"	3.75"	Rib	8"	6"	595 lbs.
W-11	16.25"	3.875"	Rib	8"	6"	550 lbs.

Standard: 1pc centered wheel hub with 5/8" roller bearings & grease fitting

Options: Wheel Hubs - 3", 4" centered with 1/2", 5/8", or 3/4" bearings

Colours: Black only



16 " Diameter 480/400-8 Diamond Tread Wheel (Standard Duty)

Diamond tire tread improves equipment's traction when operated in rough and uneven areas.

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
W-13	16.250"	3.875"	Rib	8"	6"	480 lbs

Standard: 1pc centered wheel hub with 5/8" ball bearings & grease fitting

Options: Wheel Hubs - 3", 4" centered with 1/2", 5/8", or 3/4" bearings

Colours: Black only



16 " Diameter 480/400-8 Smooth Tread Wheel (Standard Duty)

Smooth tire tread reduces compaction while rolling on soft surfaces. Ideal for golf courses and roofing equipment

Product No.	Tire Dia.	Tire Width	Tread	Rim Dia.	Hub Width	Capacity
W-12	16.750"	3.750"	Smooth	8"	6"	450 lbs

Standard: 1pc centered wheel hub with 5/8" ball bearings & grease fitting

Optional: Wheel Hubs - 3", 4" centered with 1/2", 5/8", or 3/4" bearings

Colours: Black only

*All of the above Wheelbarrow Wheel Assemblies with standard 6" wheel hubs include: 5/8" x 10.375" zinc plated cold rolled steel axle with washers & cotter pins.